



	SPRING/LOOP (WS)	VELCRO/BELTS (WV)	Q-HOOKS
Temperature Range	20 °F – 1100 °F	20 °F – 1100 °F	20 °F – 1100 °F
Surface Temperature	Up to 1000 °F	Up to 1000 °F	Up to 1000 °F
Loss in weight @1200 °F	Up to 2%	Up to 2%	Up to 2%
Thickness	Approximately 1.00"	Approximately 1.00"	Approximately 1.00"
Insulation	Type "E" Fiberglass (Asbestos Free)	Type "E" Fiberglass (Asbestos Free)	Type "E" Fiberglass (Asbestos Free)
Density	11lbs/cft	11lbs/cft	11lbs/cft
Outer Jacket	17oz Silicone Coated Thermal Cloth	17oz Silicone Coated Thermal Cloth	17oz Silicone Coated Thermal Cloth
Inner Jacket	304 SS Wire Mesh	304 SS Wire Mesh	304 SS Wire Mesh
Construction	10 ply 304 SS Thread	10 ply 304 SS Thread	10 ply 304 SS Thread
Attachment	SS Spring/Loop System	Flame resistant Velcro strips & belts with SS double D-rings	SS Quilting anchors & SS Tie Wire
Fire Resistance	Incombustible	Incombustible	Incombustible
Moisture Absorption	Negligible	Negligible	Negligible
Softening Point	1500 °F	1500 °F	1500 °F
Strain Point	1100 °F	1100 °F	1100 °F
Annealing Point	1200 °F	1200 °F	1200 °F

Special items are not refundable. All catalog items are standard sizing. Call factory for pricing on non-standard items. All weights are approximate and in pounds. Contents subject to change without notice. Minimum order amount \$50.

©2019 Innovative Exhaust Solutions, Inc. Lincoln, NE USA
 Unauthorized reproduction in full or part is strictly prohibited. | Rev030619-A

www.inExhaust.com | Phone 402.322.7022 | Fax 402.322.7032 | sales@inExhaust.com